

# Rectifier Diode


## Avalanche Diode

**V<sub>RRM</sub> = 1200-1800 V**  
**I<sub>F(RMS)</sub> = 40 A**  
**I<sub>F(AV)M</sub> = 25 A**

V <sub>RSM</sub> V	V <sub>(BR)min</sub> V	V <sub>RRM</sub> V	Anode on stud	Cathode on stud
1300	-	1200	DS 17-12A	DSI 17-12A
1300	1300	1200	DSA 17-12A	DSA 17-12A
1700	1750	1600	DSA 17-16A	DSA 17-16A
1900	1950	1800	DSA 17-18A	DSA 17-18A

① Only for Avalanche Diodes

### DO-203 AA



10-32UNF

A = Anode    C = Cathode

Symbol	Test Conditions	Maximum Ratings	
I <sub>F(RMS)</sub>	T <sub>VJ</sub> = T <sub>VJM</sub>	40	A
I <sub>F(AV)M</sub>	T <sub>case</sub> = 125°C; 180° sine	25	A
P <sub>RSM</sub>	DSA(I) types, T <sub>VJ</sub> = T <sub>VJM</sub> , t <sub>p</sub> = 10 µs	7	kW
I <sub>FSM</sub>	T <sub>VJ</sub> = 45°C; t = 10 ms (50 Hz), sine	370	A
	V <sub>R</sub> = 0 t = 8.3 ms (60 Hz), sine	400	A
	T <sub>VJ</sub> = T <sub>VJM</sub> t = 10 ms (50 Hz), sine	300	A
	V <sub>R</sub> = 0 t = 8.3 ms (60 Hz), sine	320	A
I <sup>2</sup> t	T <sub>VJ</sub> = 45°C t = 10 ms (50 Hz), sine	680	A <sup>2</sup> s
	V <sub>R</sub> = 0 t = 8.3 ms (60 Hz), sine	660	A <sup>2</sup> s
	T <sub>VJ</sub> = T <sub>VJM</sub> t = 10 ms (50 Hz), sine	450	A <sup>2</sup> s
	V <sub>R</sub> = 0 t = 8.3 ms (60 Hz), sine	430	A <sup>2</sup> s
T <sub>VJ</sub>		-40...+180	°C
T <sub>VJM</sub>		180	°C
T <sub>stg</sub>		-40...+180	°C
M <sub>d</sub>	Mounting torque	2.2-2.8 19-25	Nm lb.in.
Weight		6	g


Symbol	Test Conditions	Characteristic Values		
I <sub>R</sub>	T <sub>VJ</sub> = T <sub>VJM</sub> ; V <sub>R</sub> = V <sub>RRM</sub>	≤ 4	mA	
V <sub>F</sub>	I <sub>F</sub> = 55 A; T <sub>VJ</sub> = 25°C	≤ 1.36	V	
V <sub>To</sub>	For power-loss calculations only	0.85	V	
r <sub>T</sub>	T <sub>VJ</sub> = T <sub>VJM</sub>	8	mΩ	
R <sub>thJC</sub>	DC current	1.5	K/W	
R <sub>thJH</sub>	DC current	2.1	K/W	
d <sub>S</sub>	Creepage distance on surface	2.05	mm	
d <sub>A</sub>	Strike distance through air	2.05	mm	
a	Max. allowable acceleration	100	m/s <sup>2</sup>	

Data according to IEC 60747

IXYS reserves the right to change limits, test conditions and dimensions

© 2017 IXYS All rights reserved

### Dimensions in mm (1 mm = 0.0394")



20170323a




Fig. 1 Forward characteristics





 Fig. 2 Surge overload current  
 $I_{FSM}$ : crest value, t: duration

 Fig. 3  $I^2t$  versus time (1-10 ms)


Fig. 4 Power dissipation versus forward current and ambient temperature




Fig. 5 Max. forward current at case temperature 180° sine




Fig. 6 Transient thermal impedance junction to heatsink

 $R_{thJH}$  for various conduction angles d:

d	$R_{thJH}$ (K/W)
DC	2.10
180°	2.23
120°	2.33
60°	2.53
30°	2.72

 Constants for  $Z_{thJH}$  calculation:

i	$R_{thi}$ (K/W)	$t_i$ (s)
1	0.1006	0.0021
2	0.5311	0.0881
3	0.8683	2.968
4	0.600	3.20