
Spec Sheet

Metal Core SMD Power Inductors (MCOIL™, MD series)

MDWK4040T3R3MM



Features

- Item Summary 3.3uH±20%, 3A, 4.0x4.0x2.0mm
- Lifecycle Stage

Mass Production

Standard packaging quantity (minimum)
 Taping Embossed 700pcs

■ Products characteristics table

Inductance	3.3 uH ± 20 %
Case Size (mm)	4.0x4.0
Rated Current (max)	3 A
Saturation Current (max)	3.7 A
Saturation Current (typ)	5.2 A
Temperature Rise Current (max)	3 A
Temperature Rise Current (typ)	3.3 A
DC Resistance (max)	75 mΩ
DC Resistance (typ)	66 mΩ
LQ Measuring Frequency	1 MHz
Operating Temp. Range	-40 to +125 ℃ (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 10 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 2.0 mm
Dimension e	1.1 ±0.2 mm
Dimension f	2.5 ±0.2 mm

Recommended Land Patterns



2017.04.30

Unit: mm

Metal Core SMD Power Inductors (MCOIL™, MD series)

MCOIL™ MDWK4040T3R3MM



Dimension unit: mm unit: inch

Length: 4.0 +/- 0.2 (0.157 +/- 0.008)

Width: 4.0 +/- 0.2 (0.157 +/- 0.008)

Height: 2.0 max. (0.079 max.)

Inductance: 3.3 uH (test freq at 1MHz)
DC Resistance: 0.066 / 0.075 ohm (typ/max)
Saturation Current: 5,200 / 3,700 mA (typ/max)
Temp. rise Current: 3,300 / 3,000 mA (typ/max)
Saturation current typical: 30% reduction from initial L value.
Temp rise Current typical: Temperature will rise by 40 deg C

Maximum rated voltage: DC 25 V

