



CORE DIMENSIONS:


A 20.00 [.787] + 0.30 [.012]
B 13.00 [.512] + 0.30 [.012]
C 29.00 [1.142] + 0.50 [.020]

D 9.50 [.374] ± 0.20 [.008] E 6.240 [.246] ± 0.30 [.012]

Weight/1000 <u>24.89 kgs</u> <u>54.88 lbs.</u> (Per Pair)







CASE DIMENSIONS:

A 23.50 [.925] ± 0.40 [.016]
B 13.06 [.514] + 0.30 [.012]
C 36.25 [1.427] ± 0.50 [.020]
D 22.00 [.866] ± 0.30 [.012]


8.13 [.320] <u>+</u> REF.



UNCONTROLLED DOCUMENT

IMPEDANCE (Z)												
Frequency	25 N	1Hz	100 MHz	300 MHz								
Nominal (REF)	86	Ω	177_Ω	305 Ω								
Minimum _	-	Ω	142_Ω	- Ω								

Z vs. FREQUENCY (REF. ONLY)



FREQUENCY (MHz)

AGILENT E4991A Impedance/Material Analyzer HP 16092A-Test Fixture

NOTES:

1. CASE FLAMMABILITY RATING: UL94 V-0

2. CASE MATERIAL: HALOGEN FREE NYLON

3. ASSEMBLED PART #: 28A2913-0A2

4. CORE PART #: 28A2913-000

5. CASE COLOR: BLACK -"0A2"

6. COSMETIC SPECIFICATION REFER TO WI-QA-038.

DIMENSIONS ARE IN mm [INCHES].				This print is the property of Laird					
				Tech. and is loaned in confidence subject to return upon request					
		ļ	-	and with the understanding that no copies shall be made without	Laird				
				the written consent of Laird Tech					
				All rights to design or invention are reserved.					
				PROJECT/PART NUMBER:	REV	PART T	YPE:	DRAWN BY:	
С	UPDATE COMPANY LOGO ,ADD NOTE 6	08/23/14	QIU	28A2913-0A2	C F	FE	RRITE	TE TMB	
В	CHANGE PLASTIC CASE PLUNGER	04 /07 /11	JUN		SN		AP-ON		
	FROM TAB TO CONVEX FEATURE	04/27/11		DATE: 11/24/08	SCALE:	NTS	MATERIAL:		
Α	ORIGINAL DRAFT	11/24/08	ТМВ	CAD #	TOOL #		-	orrito	
REV	DESCRIPTION	DATE	INT	28A2913-0A2-C	,	_		errite	