

Line up

SMD type

Series	Features	Small size/Low profile	Large capacitance	Low ESR	High voltage	Long life/high reliability	Category temperature range (°C)	Rated voltage (V.DC)	ESR (mΩ)	Capacitance (μF)	Marking color	Size code	Size (mm)	
													φD	L
SVF	High voltage Large capacitance 125°C 1000 h		●		●	●	-55 to 125	16 to 25	27 to 40	27 to 82	Purple	B6	5.0	5.9
							-55 to 125	16 to 50	22 to 40	10 to 180	Purple	C6	6.3	5.9
							-55 to 125	16 to 50	22 to 35	18 to 270	Purple	E7	8.0	6.9
							-55 to 125	16 to 50	14 to 25	39 to 560	Purple	E12	8.0	11.9
							-55 to 125	16 to 50	12 to 20	68 to 1000	Purple	F12	10.0	12.6
SVPK	High voltage Large capacitance 125°C 1000 h		●		●	●	-55 to 125	25 to 50	35 to 80	10 to 33	Purple	B6	5.0	5.9
							-55 to 125	25 to 50	25 to 35	22 to 82	Purple	C6	6.3	5.9
							-55 to 125	25 to 50	24 to 35	33 to 12	Purple	E7	8.0	6.9
							-55 to 125	25 to 50	16 to 25	68 to 270	Purple	E12	8.0	11.9
							-55 to 125	25 to 50	14 to 20	120 to 470	Purple	F12	10.0	12.6
NEW SXV	Super high voltage 125 °C 1000 h				●	●	-55 to 125	100	60	6.8	Purple	E7	8.0	6.9
							-55 to 125	100	60	15	Purple	F8	10.0	7.9
							-55 to 125	63 to 100	25 to 40	15 to 33	Purple	E12	8.0	11.9
							-55 to 125	100	30	18 to 22	Purple	F12	10.0	12.6
SVPG	Low ESR High ripple current 105 °C 5000 h			●	●	●	-55 to 105	16 to 25	25 to 30	15 to 47	Purple	B45	5.0	4.4
							-55 to 105	16	8	270	Purple	C10	6.3	9.9
SVPF	High voltage Large capacitance 105 °C 5000 h		●		●	●	-55 to 105	16 to 25	27 to 40	27 to 82	Purple	B6	5.0	5.9
							-55 to 105	16 to 50	22 to 40	10 to 180	Purple	C6	6.3	5.9
							-55 to 105	16 to 50	22 to 35	18 to 270	Purple	E7	8.0	6.9
							-55 to 105	16 to 50	14 to 25	39 to 560	Purple	E12	8.0	11.9
							-55 to 105	16 to 50	12 to 20	68 to 1000	Purple	F12	10.0	12.6
SVPA	Low ESR High ripple current			●		●	-55 to 105	2.5 to 20	30 to 40	10 to 82	Purple	B6	5.0	5.9
							-55 to 105	2.5 to 20	20 to 35	22 to 180	Purple	C6	6.3	5.9
							-55 to 105	2.5 to 20	20 to 33	47 to 330	Purple	E7	8.0	6.9
							-55 to 105	2.5 to 16	19 to 29	180 to 820	Purple	F8	10.0	7.9
SVPB	Low profile	●				●	-55 to 105	2.5 to 20	40 to 45	15 to 120	Purple	C5	6.3	4.9
							-55 to 105	20	35	22	Purple	C55	6.3	5.4
SVPC	Low ESR Large capacitance		●	●		●	-55 to 105	2.5 to 16	19 to 35	39 to 180	Purple	B6	5.0	5.9
							-55 to 105	2.5 to 16	15 to 30	68 to 560	Purple	C6	6.3	5.9
							-55 to 105	2.5 to 16	19 to 27	120 to 680	Purple	E7	8.0	6.9
							-55 to 105	2.5 to 16	9 to 16	270 to 1500	Purple	E12	8.0	11.9
							-55 to 105	2.5	12	2700	Purple	F12	10.0	12.6
SVPD	Guaranteed at 125 °C High voltage 85 °C 85 % RH				●	●	-55 to 125	10 to 25	45 to 65	10 to 56	Purple	C6	6.3	5.9
							-55 to 125	16 to 35	40 to 70	8.2 to 82	Purple	E7	8.0	6.9
							-55 to 125	25 to 35	45 to 60	18 to 39	Purple	F8	10.0	7.9
							-55 to 125	25 to 35	30 to 50	22 to 47	Purple	E12	8.0	11.9
							-55 to 125	25 to 35	28 to 30	47 to 82	Purple	F12	10.0	12.6

Line up

SMD type

Series	Features	Small size/Low profile	Large capacitance	Low ESR	High voltage	Long life/High reliability	Category temperature range (°C)	Rated voltage (V.DC)	ESR (mΩ)	Capacitance (μF)	Marking color	Size code	Size (mm)	
													φD	L
SVPE	Super low ESR Large capacitance		●	●			-55 to 105	2.5 to 6.3	10 to 15	150 to 390	Purple	B6	5.0	5.9
							-55 to 105	2.5 to 10	10 to 20	220 to 390	Purple	C6	6.3	5.9
							-55 to 105	2.0 to 16	8 to 11	180 to 1200	Purple	C10	6.3	9.9
							-55 to 105	16	10	470	Purple	F12	10.0	12.6
SVPS	Long life					●	-55 to 105	4.0 to 10	200 to 220	10 to 33	Purple	A5	4.0	5.4
							-55 to 105	4.0 to 16	30 to 90	22 to 68	Purple	B6	5.0	5.9
							-55 to 105	4.0 to 20	22 to 60	22 to 150	Purple	C6	6.3	5.9
							-55 to 105	4.0 to 25	22 to 60	10 to 270	Purple	E7	8.0	6.9
							-55 to 105	4.0 to 16	20 to 35	100 to 680	Purple	F8	10.0	7.9
SVPQ	Guaranteed at 125 °C					●	-55 to 125	4.0 to 20	40 to 60	22 to 150	Purple	C6	6.3	5.9
							-55 to 125	6.3 to 20	35 to 45	47 to 220	Purple	E7	8.0	6.9
SVP	Standard						-55 to 105	4.0 to 16	200 to 260	3.3 to 33	Purple	A5	4.0	5.4
							-55 to 105	4.0 to 20	60 to 120	10 to 68	Purple	B6	5.0	5.9
							-55 to 105	2.5 to 20	23 to 60	22 to 220	Purple	C6	6.3	5.9
							-55 to 105	4.0 to 20	35 to 45	33 to 330	Purple	E7	8.0	6.9
							-55 to 105	4.0 to 20	25 to 40	56 to 680	Purple	F8	10.0	7.9
							-55 to 105	2.5 to 20	13 to 24	100 to 680	Purple	E12	8.0	11.9
							-55 to 105	2.5 to 20	12 to 20	150 to 1500	Purple	F12	10.0	12.6

Line up

Radial lead type

Series	Features	Small size/Low profile	Large capacitance	Low ESR	High voltage	Long life/high reliability	Category temperature range (°C)	Rated voltage (V.DC)	ESR (mΩ)	Capacitance (μF)	Marking color	Size code	Size (mm)	
													φD	L
SEF	High voltage Large capacitance 125°C 1000 h		●		●	●	-55 to 125	16 to 35	22 to 35	22 to 180	Purple	C6	6.3	5.9
							-55 to 125	16 to 35	22 to 30	39 to 270	Purple	E7	8.0	6.9
							-55 to 125	16 to 35	14 to 20	82 to 560	Purple	E12	8.0	11.9
							-55 to 125	16 to 35	12 to 18	120 to 1000	Purple	F13	10.0	12.9
SEPG	Low ESR High ripple current 105 °C 5000 h			●	●		-55 to 125	16	8	270	Purple	C10	6.3	9.9
NEW SXE	Super high voltage 125 °C 1000 h				●	●	-55 to 125	100	60	6.8	Purple	E7	8.0	6.9
							-55 to 125	100	60	15	Purple	F8	10.0	8.9
							-55 to 125	63 to 100	25 to 40	15 to 33	Purple	E12	8.0	11.9
							-55 to 125	100	30	18 to 22	Purple	F13	10.0	12.9
SEPF	Small size Low profile High voltage Large capacitance 105 °C 5000 h	●	●		●	●	-55 to 105	16 to 32	30 to 35	22 to 150	Purple	C55	6.3	5.4
							-55 to 105	16 to 35	22 to 35	22 to 180	Purple	C6	6.3	5.9
							-55 to 105	16 to 35	22 to 30	39 to 270	Purple	E7	8.0	6.9
							-55 to 105	16 to 35	14 to 20	82 to 560	Purple	E12	8.0	11.9
							-55 to 105	16 to 35	12 to 18	120 to 1000	Purple	F13	10.0	12.9
SEPC	Super low ESR Large capacitance Small size Low profile 105 °C 5000 h	●	●	●		●	-55 to 105	2.5	7	100 to 560	Purple	B9	5.0	8.9
							-55 to 105	6.3	18	220	Purple	C55	6.3	5.4
							-55 to 105	2.5 to 16	10 to 24	100 to 560	Purple	C6	6.3	5.9
							-55 to 105	2.5 to 16	7 to 10	100 to 820	Purple	C9	6.3	8.9
							-55 to 105	2.5 to 16	8 to 22	150 to 1000	Purple	E7	8.0	6.9
							-55 to 105	2.5 to 16	5 to 10	180 to 1000	Purple	E9	8.0	8.9
							-55 to 105	16	11 to 16	180 to 270	Purple	E12	8.0	11.9
							-55 to 105	2.5 to 6.3	7 to 8	470 to 820	Purple	E13	8.0	12.9
SEQP	105 °C 5000 h Guaranteed at 125°C Rated 32 V.DC max.				●	●	-55 to 125	4.0 to 20	40 to 60	22 to 150	Purple	C6	6.3	5.9
							-55 to 125	4.0 to 32	35 to 100	6.8 to 330	Purple	E7	8.0	6.9
							-55 to 125	4.0 to 32	25 to 80	15 to 680	Purple	F8	10.0	7.9
							-55 to 125	4.0 to 32	13 to 50	18 to 560	Purple	E12	8.0	11.9
							-55 to 125	4.0 to 20	12 to 20	150 to 1200	Purple	F13	10.0	12.9
SEP	Standard				●	●	-55 to 105	4.0 to 20	40 to 60	22 to 150	Purple	C6	6.3	5.9
							-55 to 105	4.0 to 20	35 to 45	33 to 330	Purple	E7	8.0	6.9
							-55 to 105	4.0 to 20	25 to 40	56 to 680	Purple	F8	10.0	7.9
							-55 to 105	2.5 to 20	13 to 24	100 to 680	Purple	E12	8.0	11.9
							-55 to 105	2.5 to 20	12 to 20	150 to 1500	Purple	F12	10.0	12.9