

Silicon Power Schottky Diode

$V_{RRM} = 20 \text{ V - } 100 \text{ V}$
 $I_F = 80 \text{ A}$

Features

- High Surge Capability
- Types up to 100 V V_{RRM}

DO-5 Package



Maximum ratings, at $T_j = 25^\circ\text{C}$, unless otherwise specified ("R" devices have leads reversed)

Parameter	Symbol	Conditions	MBR8045 (R)	MBR8060 (R)	MBR8080 (R)	MBR80100 (R)	Unit
Repetitive peak reverse voltage	V_{RRM}		45	60	80	100	V
RMS reverse voltage	V_{RMS}		32	42	50	70	V
DC blocking voltage	V_{DC}		45	60	80	100	V
Continuous forward current	I_F	$T_C \leq 120^\circ\text{C}$	80	80	80	80	A
Surge non-repetitive forward current, Half Sine Wave	$I_{F,SM}$	$T_C = 25^\circ\text{C}, t_p = 8.3 \text{ ms}$	1000	1000	1000	1000	A
Operating temperature	T_j		-65 to 150	-65 to 150	-65 to 150	-65 to 150	$^\circ\text{C}$
Storage temperature	T_{stg}		-65 to 175	-65 to 175	-65 to 175	-65 to 175	$^\circ\text{C}$

Electrical characteristics, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	MBR8045 (R)	MBR8060(R)	MBR8080 (R)	MBR80100 (R)	Unit
Diode forward voltage	V_F	$I_F = 80 \text{ A}, T_j = 25^\circ\text{C}$	0.65	0.75	0.84	0.84	V
Reverse current	I_R	$V_R = 20 \text{ V}, T_j = 25^\circ\text{C}$ $V_R = 20 \text{ V}, T_j = 125^\circ\text{C}$	5 250	5 250	5 250	5 250	mA
Thermal characteristics							
Thermal resistance, junction - case	R_{thJC}		1.0	1.0	1.0	1.0	$^\circ\text{C/W}$

