

## Normally – OFF Silicon Carbide Super Junction Transistor


$V_{DS}$	=	<b>650 V</b>
$V_{DS(ON)}$	=	<b>1.7 V</b>
$I_D$	=	<b>4 A</b>
$R_{DS(ON)}$	=	<b>415 mΩ</b>

### Features

- 250 °C maximum operating temperature
- Temperature independent switching performance
- Electrically isolated base-plate
- Gate oxide free SiC switch
- Suitable for connecting an anti-parallel diode
- Positive temperature coefficient for easy paralleling
- Low gate charge
- Low intrinsic capacitance

### Package

- RoHS Compliant



**TO – 257 (Isolated Base-plate Hermetic Package)**

### Advantages

- Low switching losses
- Higher efficiency
- High temperature operation
- High short circuit withstand capability

### Applications

- Down Hole Oil Drilling, Geothermal Instrumentation
- Hybrid Electric Vehicles (HEV)
- Solar Inverters
- Switched-Mode Power Supply (SMPS)
- Power Factor Correction (PFC)
- Induction Heating
- Uninterruptible Power Supply (UPS)
- Motor Drives

### Maximum Ratings at $T_j = 250\text{ °C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Values	Unit
Drain – Source Voltage	$V_{DS}$	$V_{GS} = 0\text{ V}$	650	V
Continuous Drain Current	$I_D$	$T_C = 165\text{ °C}$	4	A
Gate Peak Current	$I_{GM}$		5	A
Reverse Gate – Source Voltage	$V_{GS}$		200	V
Reverse Drain – Source Voltage	$V_{DS}$		40	V
Power Dissipation	$P_{tot}$	$T_C = 25\text{ °C}$	7	W
Operating and Storage Temperature	$T_j, T_{stg}$		-55 to 250	°C

### Electrical Characteristics at $T_j = 250\text{ °C}$ , unless otherwise specified



Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
<b>On Characteristics</b>						
Drain – Source On Voltage	$V_{DS(ON)}$	$I_D = 4\text{ A}, I_G = 100\text{ mA}, T_j = 25\text{ °C}$		1.7		V
		$I_D = 4\text{ A}, I_G = 250\text{ mA}, T_j = 175\text{ °C}$		3.2		
		$I_D = 4\text{ A}, I_G = 250\text{ mA}, T_j = 250\text{ °C}$		4.7		
Drain – Source On Resistance	$R_{DS(ON)}$	$I_D = 4\text{ A}, I_G = 100\text{ mA}, T_j = 25\text{ °C}$		415		mΩ
		$I_D = 4\text{ A}, I_G = 250\text{ mA}, T_j = 175\text{ °C}$		820		
		$I_D = 4\text{ A}, I_G = 250\text{ mA}, T_j = 250\text{ °C}$		1310		
Gate Forward Voltage	$V_{GS(FWD)}$	$I_G = 500\text{ mA}, T_j = 25\text{ °C}$		3.3		V
		$I_G = 500\text{ mA}, T_j = 250\text{ °C}$		3.2		
DC Current Gain	$\beta$	$V_{DS} = 5\text{ V}, I_D = 5\text{ A}, T_j = 25\text{ °C}$		120		
		$V_{DS} = 5\text{ V}, I_D = 5\text{ A}, T_j = 250\text{ °C}$		85		

### Off Characteristics

Drain Leakage Current	$I_{DSS}$	$V_R = 650\text{ V}, V_{GS} = 0\text{ V}, T_j = 25\text{ °C}$		7	nA
		$V_R = 650\text{ V}, V_{GS} = 0\text{ V}, T_j = 175\text{ °C}$		25	
		$V_R = 650\text{ V}, V_{GS} = 0\text{ V}, T_j = 250\text{ °C}$		105	

**Electrical Characteristics at  $T_J = 250\text{ }^\circ\text{C}$ , unless otherwise specified**

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
<b>Dynamic Characteristics</b>						
Input Capacitance	$C_{iss}$	$V_{DS} = 35\text{ V}, V_{GS} = 0\text{ V},$ $f = 1\text{ MHz}, T_{vj} = 25\text{ }^\circ\text{C}$		324		pF
Output Capacitance	$C_{oss}$			45		pF
Reverse Transfer Capacitance	$C_{rss}$			45		pF
<b>Switching Characteristics</b>						
Turn On Delay Time	$t_{d(on)}$	$V_{DD} = 400\text{ V}, I_D = 5\text{ A},$ $R_{G(on)} = R_{G(off)} = 44\text{ }\Omega,$ $V_{GS} = -8/15\text{ V}, T_J = 175\text{ }^\circ\text{C}$ Refer to Figure 10 for gate drive current waveforms		5		ns
Rise Time	$t_r$			15		ns
Turn Off Delay Time	$t_{d(off)}$			74		ns
Fall Time	$t_f$			14		ns
Turn-On Energy Per Pulse	$E_{on}$			24		$\mu\text{J}$
Turn-Off Energy Per Pulse	$E_{off}$		7		$\mu\text{J}$	
Total Switching Energy	$E_{ts}$		31		$\mu\text{J}$	
Turn On Delay Time	$t_{d(on)}$	$V_{DD} = 400\text{ V}, I_D = 5\text{ A},$ $R_{G(on)} = R_{G(off)} = 44\text{ }\Omega,$ $V_{GS} = -8/15\text{ V}, T_J = 250\text{ }^\circ\text{C}$ Refer to Figure 10 for gate drive current waveforms		9		ns
Rise Time	$t_r$			24		ns
Turn Off Delay Time	$t_{d(off)}$			114		ns
Fall Time	$t_f$			17		ns
Turn-On Energy Per Pulse	$E_{on}$			54		$\mu\text{J}$
Turn-Off Energy Per Pulse	$E_{off}$		10		$\mu\text{J}$	
Total Switching Energy	$E_{ts}$		64		$\mu\text{J}$	
<b>Thermal Characteristics</b>						
Thermal resistance, junction - case	$R_{th(jc)}$		4.2			$^\circ\text{C/W}$


**Figure 1: Typical Output Characteristics at 25 °C**

**Figure 2: Typical Output Characteristics at 175 °C**




Figure 3: Typical Output Characteristics at 250 °C




Figure 4: Typical Gate Source I-V Characteristics vs. Temperature




Figure 5: Normalized On-Resistance and Current Gain vs. Temperature




Figure 6: Typical Blocking Characteristics




Figure 7: Typical Capacitance vs Drain-Source Voltage






Figure 8: Typical Turn On Energy Losses and Switching Times vs. Temperature




**Figure 9: Typical Turn Off Energy Losses and Switching Times vs. Temperature**



**Figure 10: Typical Gate-Source Switching Waveforms**

**Package Dimensions:**



**NOTE**  
1. CONTROLLED DIMENSION IS INCH. DIMENSION IN BRACKET IS MILLIMETER.  
2. DIMENSIONS DO NOT INCLUDE END FLASH, MOLD FLASH, MATERIAL PROTRUSIONS

**Revision History**

Date	Revision	Comments	Supersedes
2012/08/24	0	Initial release	

## Published by

GeneSiC Semiconductor, Inc.  
43670 Trade Center Place Suite 155  
Dulles, VA 20166

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice.

GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.