

Silicon Bridge Rectifier

V_{RRM} = 50 V - 1000 V

I_F = 1 A

Features

- Types up to 1000 V V_{RRM}
- Ideal for printed circuit board
- High surge current capability
- High temperature soldering guaranteed: 250°C/ 10 seconds
- Small size, simple installation

DB Package



Mechanical Data

Case: Molded plastic

Polarity: Polarity symbols marked on body

Mounting position: Any

Terminals: Plated leads, solderable per MIL-STD-202

Method 208 guaranteed

Maximum ratings, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	DB105G	DB106G	DB107G	Unit
Repetitive peak reverse voltage	V _{RRM}		600	800	1000	V
RMS reverse voltage	V _{RMS}		420	560	700	V
DC blocking voltage	V _{DC}		600	800	1000	V
Continuous forward current	I _F	T _C ≤ 40 °C	1	1	1	A
Surge non-repetitive forward current, Half Sine Wave	I _{F,SM}	T _C = 25 °C, t _p = 8.3 ms	30	30	30	A
Operating temperature	T _j		-65 to 150	-65 to 150	-65 to 150	°C
Storage temperature	T _{stg}		-65 to 150	-65 to 150	-65 to 150	°C

Electrical characteristics, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	DB105G	DB106G	DB107G	Unit
Diode forward voltage	V _F	I _F = 1 A, T _j = 25 °C	1.1	1.1	1.1	V
Reverse current	I _R	V _R = 50 V, T _j = 25 °C	5	5	5	μA
		V _R = 50 V, T _j = 125 °C	500	500	500	
Thermal characteristics						
Thermal resistance, junction - case	R _{thJC}		20.00	20.00	20.00	°C/W

