

## Axial Leaded Ceramic Capacitors

## UP050CH560J-A-BZ



## ■ Features

- Item Summary  
56pF±5%, 50V,  
CH, φ 2.2x3.2mm
- Lifecycle Stage  
Non-preferred
- Standard packaging quantity (minimum)  
Taping 3000pcs

## ■ Products characteristics table

|                                  |               |
|----------------------------------|---------------|
| Capacitance                      | 56 pF ± 5 %   |
| Case Size (mm)                   | 2.2x3.2       |
| Rated Voltage                    | 50 V          |
| Q (min)                          | 1000 at 1MHz  |
| Temperature Characteristic (JIS) | CH            |
| Operating Temp. Range (JIS)      | -25 to +85 °C |
| Temperature Characteristic       | 0 ±60 ppm/°C  |
| Insulation Resistance (min)      | 10 GΩ         |
| RoHS2 Compliance (10 subst.)     | Yes           |
| REACH Compliance (173 subst.)    | Yes           |
| Soldering                        | Wave          |

## ■ External Dimensions

|             |                 |
|-------------|-----------------|
| Dimension D | Max φ 2.2 mm    |
| Dimension L | Max 3.2 mm      |
| Dimension d | φ 0.45 ±0.05 mm |

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
 Before making final selection, please check product specification.