







Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939 Fax:

SMD24LHE **THRU** SMD210LHE

2 Amp

Schottky Rectifiers 40 - 100 Volts

SOD-123HE

DIMENSIONS								
DIM	INCHES		MM		NOTE			
	MIN	MAX	MIN	MAX				
Α	.140	.156	3.55	3.95				
В	.100	.112	2.55	2.85				
С	.035	.043	0.90	1.10				
D	.067	.075	1.70	1.90				
Е	.028	.035	0.70	0.90				
F	.004	.008	0.10	0.20				
G	.001	.002	0.02	0.05				
Н	.067	.098	1.70	2.50				
J	.016	.047	0.40	1.20				

Features

- Halogen free available upon request by adding suffix "-HF"
- High current capability.
- Lead Free Finish/RoHS Compliant (Note1)("P"Suffix designates Compliant. See ordering information)
- Guardring for overvoltage protection.
- Silicon epitaxial planar chip, metal silicon junction. Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Typical Thermal Resistance: 13°C/W Junction to Lead

MCC Catalog Number	Device Marking	Maximum Recurrent Peak Reverse	Maximum RMS Voltage	Maximum DC Blocking
		Voltage		Voltage
SMD24LHE	SL24L	40V	28V	40V
SMD26LHE	SL26L	60V	42V	60V
SMD210LHE	SL210L	100V	70V	100V


Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Forward Current	I _{F(AV)}	2.0A	See Fig.1
Peak Forward Surge Current	I _{FSM}	50A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V _F SMD24LHE SMD26LHE SMD210LHE	0.47V 0.55V 0.72V	I _{FM} = 2.0A;
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	0.5mA	T _J = 25°C


Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.




Characteristics(Typical)











Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.